



Recommended PCB Layout (Top View)

Part Number	Contact Area Plating Finish
K22X-E9S-N	Gold Flash (Standard)
K22X-E9S-N15	15u" Gold (15 Option)
K22X-E9S-N30	30u" Gold (30 Option)

Material and Finish

Insulator: PBT Thermoplastic with Glass-fiber Reinforcement, UL 94V-0 Rated, Color: Black

Shell: Steel, Tin Plated

Contact Material: Socket - Phosphor Bronze

Contact Plating Options:

Standard: Gold Flash on Mating End, Tin on Termination End, Nickel Underplate on Entire Contact

15 Option: 15u" Gold on Mating End, Tin on Termination End, Nickel Underplate on Entire Contact

30 Option: 30u" Gold on Mating End, Tin on Termination End, Nickel Underplate on Entire Contact

Electrical Specifications

- Rated Current: 2A
- Rated Voltage: 30V RMS
- Insulation Resistance: 1000 Megohms Min. at 500V DC
- Contact Resistance: 13 milliohms Max.
- Dielectric Withstanding Voltage: 1000V for 1 Minute

Mechanical Specifications

Operating Temperature: -55°C to +105°C



Tolerances
X.X ± 0.25
X.XX ± 0.15
Unless Stated Otherwise

REV.	DATE	DESCRIPTION	REV. BY	CHK. BY	DRAWN BY	DATE
A1	05/06/05	New Drawing	H. MA	C. Furumasa	H. MA	05/06/05
A2	02/21/08	ECO #07-049	S. Vien	H. MA		
A3	07/29/13	ECO #12-018	S. Vien	P. DalCanto		

K22X-E9S-Nxx

Right Angle D-Sub, RoHS Compliant

9 Position Female, 0.318" Footprint

