



Material and Finish

Body: ABS Thermoplastic
 UL94 HB Rated
 Color: Black

Inner Shield: Copper Alloy,
 Nickel Plated

Insert: Nylon, Black Color
 UL94 V-2 Rated

Contacts: Brass

Contacts Plating Options:
 Silver Plating

Operating Temperature:
 -40°C to +85°C

Electrical Characteristics

Contact Rating (Per Pin):
 7.5A Max. @ 48V DC

Insulation Resistance:
 50 Megohms Min. at 250V DC

Dielectric Withstanding Voltage:
 500 V AC RMS for 1 Minute

Contact Resistance:
 30 milliohms Max.

Recommended Wire AWG.
 18 AWG. for Power Wire

RoHS COMPLIANT

Tolerances
X.X ± 0.35
X.XX ± 0.25
Unless Stated
Otherwise

REV.	DATE	DESCRIPTION	REV. BY	CHK. BY	DRAWN BY	DATE
A9	01/31/13	ECO #13-006	S. Vien	P. DalCanto	R. Aguirre	06/30/05
A10	11/27/13	ECO #13-095	D. Gih	H. MA		
A11	12/04/13	ECO #13-097	D. Gih	H. MA		
A12	01/08/15	ECO #15-003	W. Cook	H. MA		
A13	02/29/16	ECO #16-005	C. Kelleher	W. Cook	UNITS	mm
A14	04/10/17	Remove 30u" option	H. MA	N/A		

KPPX-4P

Power Plug, Cable Mount
 Snap and Lock, RoHS Compliant

